



Viro Thatch Tile	\$34.50
Viro Thatch Sub-Tile	\$15.95
Viro Top Piece (Moulded & Ridged)	\$125.00

Thatch Price per SQM - Tile	\$149.00
Thatch Price per SQM - Sub-Tile	\$104.00

Viro Thatch Tile



Viro Thatch Sub-Tile



Viro Moulded Top Piece



Viro Ridged Top Piece



Viva Palm Tile	\$21.95
Viva Palm Hip/Ridge Piece	\$21.95

Thatch Price per SQM	\$137.00
----------------------	----------

Viva Palm Tile



Viva Palm Hip/Ridge Piece



Viro Thatch - Synthetic

Viro Thatch Synthetic Bali ties are an excellent long lasting alternative to both natural African & Bali Thatch.

Viro thatch is manufactured into a 780 x 600mm flexible tile, which can be clipped, stapled, or nailed onto existing structures for quick, no-fuss installation.

The Viro thatch sub-tiles are 780 x 600mm, for use over an existing roof structure such as colorbond to provide that great aesthetic look of thatch.

- 95% waterproof, and wind-resistant.
- Natural insulation offering maximum UV.
- No condensation – making it an ideal application for alfresco areas, and spas.
- Long lifespan and durability.
- 15 years manufacturer’s warranty

Recommended Thatch Spacing	300mm (Tile) 200mm (Sub-Tile)
Recommended Minimum Roof Pitch	30 degrees
Recommended Rafter Spacing	500 – 650mm

Viva Palm - Synthetic

Viva Palm by Enduroreed is an excellent alternative to natural Bali Thatch for those wanting the durability of synthetic thatching with the added advantage of 100% waterproofing and fire resistance.

This unique synthetic roofing thatch is formed into a textured shingle and then cut with a pattern to replicate the appearance of natural palm leaves.

Used in resorts around the world including Four Seasons, Aussie World, Disneyworld Hong Kong, and Nashville Zoo, this quality synthetic is suited for commercial projects and backyard renovations alike.

- 20 years manufacturer’s warranty.
- Class A Fire Rating (USA), and Australian Fire Test Certificate.
- Wind and weather resistant.
- 100% recyclable.
- Maintenance free.
- Fast, easy installation.

Recommended Thatch Spacing	200mm
Recommended Minimum Roof Pitch	30 degrees
Recommended Rafter Spacing	500 – 650mm